

DNV 2.7-1 Workshop Container

Equipment Overview

Byrne's workshop containers are ideal for supporting regular plant maintenance, TAR/shutdowns or site construction and new build projects, offering a workplace solution right where it is needed, ensuring operational downtime is minimised.

Fitted out with a bench and vice, lockable cupboard shelving storage, lighting and power sockets, there is a central runway beam complete with low headroom trolley / electric hoist and anti-slip studded rubber mat flooring.

Designed and manufactured in accordance with DNV 2.7-1 / EN12079 the containers are suitable for both offshore lifting and intermodal road, sea & rail freight handling and transportation.

Forklift pockets offer a choice of handling equipment and a certified sling and shackle set is fitted as standard.



Specifications

Equipment	External Dimensions (L x W x H)	Internal Dimensions (L x W x H)	Tare	Payload	M.G.W	Internal Cubic Capacity
10ft Workshop Container - Type 1	2.99 x 2.43 x 2.59 m 9'9" x 8' x 8'6" ft	2.83 x 2.24 x 2.32 m 9'3" x 7'7" x 7'7" ft	2,200 kgs 4,850 lbs	7,800 kgs 17,195 lbs	10,000 kgs 22,045 lbs	14.7 m ³ 519 cu.ft
10ft Workshop Container - Type 2	2.99 x 2.43 x 2.59 m 9'9" x 8' x 8'6" ft	2.80 x 2.28 x 2.23 m 9'2" x 7'5" x 7'4" ft	2,200 kgs 4,850 lbs	7,800 kgs 17,195 lbs	10,000 kgs 22,045 lbs	14.3 m ³ 504 cu.ft
20ft Workshop Container - Type 1	6.05 x 2.43 x 2.59 m 19'10" x 8' x 8'6" ft	5.89 x 2.24 x 2.32 m 19'2" x 7'7" x 7'4" ft	3,650 kgs 8,050 lbs	10,000 kgs 22,040 lbs	13,650 kgs 30,100 lbs	30.8 m ³ 1087 cu.ft
20ft Workshop Container - Type 2	6.05 x 2.43 x 2.59 m 19'10" x 8' x 8'6" ft	5.86 x 2.30 x 2.21 m 19'2" x 7'6" x 7'3" ft	3,700 kgs 8,157 lbs	10,000 kgs 22,040 lbs	13,700 kgs 30,203 lbs	30.0 m ³ 1059 cu.ft

Key Features

Equipment	Specification	Key Features
Workshop Container	DNV 2.7-1, BS EN 12079 & ISO/CSC	<p>Design, Manufacture & Certification</p> <ul style="list-style-type: none"> - DNV 2.7-1 offshore containers - BS EN 12079:2006 offshore containers: Design, construction, testing, inspection and marking - Classification Society: Lloyds Register - Certification: Third party lifting certification provided for container and sling set <p>Other Features</p> <ul style="list-style-type: none"> - Insulation: PU sandwich panels, 50mm thick on sides and 100mm on roof - Electrics: Lighting, switch and power sockets 110v & 240V round plug/pin options - safe area - Work Area: Work bench complete with vice and under bench storage shelves - Storage: Removable, bolted floor to roof storage cupboard with shelving and double doors - Lifting: Central runway beam complete with low headroom trolley / electric hoist - 1.0Te SWL with chain bag - Safety: Anti-slip studded rubber mat floor - Storage: Stackable to minimise deck area usage on location - Welfare: AC units built into type 2 units

UAE

Dubai +971 4 454 4800
Abu Dhabi +971 2 614 0100
Fujairah +971 9 222 8163

KSA

Jubail +966 13 362 5245
Dammam +966 13 340 4888
Riyadh +966 11 810 8931
Jeddah +966 12 641 1860
Yanbu +966 14 321 1666
Turaif +966 50 478 8054
Jizan +966 55 880 1257

KUWAIT

Fahaheel +965 222 52190

OMAN

Muscat +968 2 689 3082
Duqm +968 2 689 3082

BAHRAIN

Manama +973 172 80890



Enabling operational efficiency through equipment rental and lease solutions

UAE ■ KSA ■ Kuwait ■ Oman ■ Bahrain